QUICK REFERENCE GUIDE > DD24SI9 N

# Integrated Single DishDrawer Dishwasher, Sanitize

Series 9 | Integrated

Panel Ready



A compact size to fit anywhere, room to wash a half load, and less bending.

- · Knock to pause function is perfect if you miss a dish
- Six wash programs, as well as additional Quick wash, Sanitize and Extra Dry options
- Customize with your own kitchen cabinetry or purchase our stainless steel door panel accessory


 American Disabilities Act (ADA) compliant, this can be installed at an accessible height for loading and unloading

#### **DIMENSIONS**

Height 16 1/8 "

Width 23 9/16 "

Depth 21 3/4 "



#### **FEATURES & BENEFITS**

#### Seamless integration

Slide your DishDrawer™ Dishwasher into an existing kitchen space or integrate into kitchen cabinetry, for a seamless look whilst delivering superior dish care.

Ease of use

DishDrawer™ Dishwashers are as easy to open and close as kitchen drawers and can be conveniently positioned at bench height for ease of loading and minimal bending. Flexible racking allows you to make adjustments to fit in a variety of dishes.

### **Quick, Sanitise and Extra Dry options**

The Quick wash modifier delivers a faster wash while maintaining performance. The Sanitise option provides extra protection killing 99.9% of bacteria in the final rinse. The Extra Dry setting is perfect for plastic dishes.

#### Knock to pause

Instead of needing a remote control, these DishDrawer™ Dishwashers have a knock to pause function. A knock on the front panel will pause the dishwasher which can be re-started again by using the start/play button.

#### Quiet performer

Running at a very low decibel rate, these DishDrawer™ Dishwashers do their job without making a fuss. The combination of intelligent technology and simple mechanics means greater reliability and excellent wash performance.

#### **SPECIFICATIONS**

#### Accessories (included)

Cutlery basket

Knife clip and multipurpose clip

•

#### Accessories (sold separately)

Door panel stainless steel ADDD24SPX
Handle kit Classic AHCL-DDDW-24X
Handle kit Contemporary round, aluminium AHS-OBDD-60S

QUICK REFERENCE GUIDE > DD24SI9 N Date: 20.06.2024 > 2

Handle kit Contemporary square fine, aluminium	AHD5- OBDD-60SX	Keylock	•	Safety and compliance	
Handle kit Contemporary square fine, black		Knock to pause	•	ADA compliant	•
naticie kit Contemporary square fille, black	OBDD-60SB	Rinse aid indicator light	•		
Handle kit Contemporary square, aluminiumAHD3-OBDD-60S		Smart appliance	•		
Handle kit Professional round flush	AHP3-DWDD-SX	Wi-Fi connectivity	•	Warranty	
Handle kit Professional round flush, Brass off-stands	AHP3DDDW24BA			Parts and labor	Limited 2 years
Handle kit Professional round flush, Dark Copper off-stands	AHP3DDDW24DC	Features			
		Fan assisted drying	•	Wash Program Modifiers	
		Flow through detergent dispenser	•	Extra Dry	•
Capacity and loading		Quiet operation	•	Quick	•
Accommodates round plates up to	11"	SmartDrive <sup>™</sup> technology	•	Sanitise	•
Adjustable height, foldable cupracks	•			Wash modifiers	3
Fold down tines	•				
Pitch adjustable tines	•	Performance			
Place settings	7	Noise emissions	43 dBA	Wash Programs	
Place settings	7			Delicate	•
				Eco	•
		Power requirements		Fast	•
Consumption		Amperage	5A	Heavy	•
Energy usage	144kWh/year	Electric circuit	3 wire	Medium	•
In-use energy carbon emissions estimate	17.8kgCO2e/year	Rated current	15 A	Rinse	•
Water usage (per wash cycle)	1.64 gal	Supply frequency	60Hz	Wash programs	6
Trailer adage (per trailer eyere)		Supply voltage	100 - 120V		
Controls				Water connection	
Electronic fault/Diagnostic indicator		Product dimensions		Inlet water temperature	Max 140 °F
End of cycle beeps		Depth	21 3/4 "	Supplied hose to suit 3/8" (9mm) male	•
Energy saving delay start option of up to 12	•	Height	16 1/8 "	compression fitting	
hours	•	Width	23 9/16 "	Water pressure	30kPa - 1000 kPa
Internal wash selector	•				

QUICK REFERENCE GUIDE > DD24SI9 N Date: 20.06.2024 > 3

water supply	3/8" to suit Male Compression Fitting
CIAL	007.40
SKU	82342

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

#### Other product downloads available at fisherpaykel.com

2D-DWG Integrated Single DishDrawer™ Dishwasher

2D-DXF Integrated Single DishDrawer™ Dishwasher

Data Sheet Integrated Single DishDrawer™ Dishwasher

Energy Label Single DishDrawer™ Dishwasher

J Installation Guide DishDrawer™ Dishwasher Venting Kit EN

Installation Guide Single Dish Drawer EN

J. Guide d'installation FR

↓ Planning Guide Integrated Single DishDrawer™

Planning Guide Professional Style Dial/Handle Accessories

L. Quick Start Guide

Revit Single DishDrawer™ Dishwasher

Rhino Single DishDrawer™ Dishwasher

Rhino Single DishDrawer™ Dishwasher with Door Panel and Contemporary Square Handle

J. Sketchup Single DishDrawer™ Dishwasher

Sketchup Single DishDrawer™ Dishwasher with Door Panel and Contemporary Square Handle



User Guide DishDrawer™ Dishwasher EN

#### Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



## A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com